










<b>Model</b>	<b>EG2048KSZ (48V)</b>			
<b>General Specifications:</b>				
Passenger capacity	6			
Range (loaded) based on flat road at	>70			
Max. speed (km/h)	32			
Minimum turning radius (m)	4,5			
Max. climbing ability (loaded)	20 %			
Max. movement after brake	≤4m			
Overall dimensions	3500x1180x1850mm			
Max. loading weight	450kgs			
Net weight	570kgs			
Qty/20'	4			
Qty/40'	10			
Qty/40'HQ	16			
<b>Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration )</b>				
<b>PART DESCRIPTIONS</b>				
Body	Steel framework + plastic front body +fiberglass rear body			
Roof	Fibreglass plastic			
Windshield	one-piece Organic glass			
Windshield, hinged	\			
Stainless steel package	including front upright, rear upright			
2point seat belt	\			
Large Seats:				
1) backrest and cushion	Reborn seat + artificial leather			
2) armrest	Formed			
3) plastic seat bottom				
Backrest in wood finish	\			
Floor mat	rubber			
Dashboard in black plastic finish	forward/reverse switch, battery capacity indicator, ignition key			
Dashboard in wood finish	wood finish			
Steering wheel in wood finish	\			
Beverage holders	4 cups drink holders			
Lighting system and horn	2 headlights, 2 front turn signals, 2 taillights( each combined 1 brake light with 1 turn signal), with DC-DC converter (converting from 48V to 12V), horn			
Glove box	\			
Side trim	stainless steel			
	Aluminum			
Score card holder	on steering wheel			
Towing bracket	on front of golf car			
Battery	Trojan battery T605 X 8PCS			
If with T105 battery	Trojan battery T105 X 8PCS			
Motor	4KW			
Controller	Curtis brand 1268			
12V accessory plug	to be mounted on the dashboard			
Hour meter	\			
Steering system	Single-stage rack and pinion steering system, automatic rocker compensating function			
Brake system	Mechanical brake			
	4-wheel hydraulic brake + hand brake			
	4-wheel hydraulic brake, front disc brake, rear drum brake			
Accelerator	Stepless speed change			
Suspension system	Front and rear plate spring + vibration absorber			
Driving mode	Rear axle two stage deceleration, motor direct driving			
Rear axle	Gear ratio12.49:1			
	New gear ratio 10.25, working together with 48V/4KW motor to get high speed of 40km/h or 25mp		NO extra cost	
side rear view mirror	\			
Wheel & Tyre	10x7 Alumimum wheel & 205/50-10 4PR			

Note: above photo is not right, only for reference to the style.

	6J-10 steel wheel with cap & 205/50-10 4PR		
	8*7 steel wheel with cap & 18*8.5-8 4PR		
	8*7 steel wheel with cap & 18*8.5-8 6PR		
Reversing alarm	\		
Cooler	\		
Enclosure	\		

**ACCESSORIES:**

Charger	China origin, input 110V-240V~50Hz-60Hz, output 48V, 25A		
	Imported on-board charger		
1pc density checker for battery	to be provided at the half of the order quantity		