


Model	EG6020A4D			
Descriptions:	HUNTING BUGGY			
General Specifications:				
Passenger capacity	4			
Voltage (V)	48V			
Range (loaded) based on flat road at a speed	60			
Max. speed (km/h)	40			
Max. climbing ability (loaded)	30 %			
Wheelbase	1660mm(65inch)			
Length	3030mm(119inch)			
Width	1395mm(55inch)			
Height	1990mm(78inch) for top without search light, 2225mm(87.5inch) for top with search light.			
Dry Weight	770kgs(1698lbs)			
Turning Radius	3.8m (150inch)			
Ground Clearance	215mm(8.5inch) at rear end, 320mm(12.6inch) at brake oil pump.			
Clearance @ center of frame	415mm(16inch)			
Max. loading weight	400kgs(882lbs)			
Container quantity:				
Qty/40'	12PCS			
Configurations: ("S" stands for Standard configuration and "O" stands for Optional configuration)				
PART DESCRIPTIONS				
Body	Steel framework + injected plastic			
Body color (front body and rear body)	camouflaged			
	solid color			
Roof frame	steel structure in solid color			
Roof frame in camo	steel structure in camo			
Roof	canvas			
	fibreglass roof in solid color			
	fibreglass roof in camo color			
3points seat belt	2 pcs per car			
Windshield	one-piece see-through, with holder			
	Foldable windshield, with holder			
Seats:				
1) backrest and cushion	Sponge + artificial leather			
mark: backrest and cushion in camo	\			
2) armrest	plastic			
3) rear foldable seat	aluminum rear board			
Side fender in camo(both side)	\			
Dashboard in black plastic finish	\			
Instrument on dashboard	battery power meter, power key, F/R switch, 4WD and 2WD switching button, winch switch; switch for searchlight (option)			
Beverage holders	4 cups drink holders			
front metallic bumper	steel			
front metallic bumper in camo	steel			
metallic steel guard above front body	steel			
Gun holder	\			
Lighting system and horn	headlight, front turn light, tail light, horn and reverse alarm			
Winch	\			
Searchlight	4pcs			
Battery	Trojan battery T105 X 8pcs			
Motor	4KW x 2			
Controller	Curtis 1244 x 2			
Brake system	4 wheel hydraulic disc brake			
Accelerator	Stepless speed change			
Suspension system	Front and rear independent suspension			
Driving mode	Front axle drive and rear axle drive (4x4)			
Gear ratio	10.25: 1			
Wheel and tyre	12x7 Steel wheel, 25 x 8-12 tyre			
Rim in camo(four pcs)	12x7 Steel wheel			
side rear-view mirror	\			
inner view mirror	\			
ACCESSORIES:				
Charger	China origin, input 110V-240V~50Hz-60Hz, output48V, 25A			
1pc density checker for battery	\			